



General ordering data

| | |
|------------------|--|
| Order No. | 1797320000 |
| Part designation | SL-SMT5.00/11/90LF 1.5SN |
| Version | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 11, 90°, Box |
| EAN | 4032248238101 |
| Qty. | 50 pc(s). |

System parameters

| | |
|-----------------------------|--------------------------|
| Fitted to PCB | Reflow solder connection |
| Outgoing elbow | 90° |
| Pitch | 5 mm |
| Pitch in inch | 0.197 inch |
| No. of poles | 11 |
| Solder pin length | 1.5 mm |
| Can be coded | Yes |
| No. of rows | 1 |
| No. of solder pins per pole | 1 |
| Fitting hole tolerance | + 0.1 mm |
| L1 in mm | 50 mm |
| L1 in inch | 1.969 inch |
| Insulation resistance | 1 MΩ |

Material data

| | |
|--------------------------------|---------------------|
| Insulating material | LCP GF |
| Colour | black |
| colour chart | Similar to RAL 9011 |
| Insulating material group | IIIa |
| Flammability class UL 94 | V-0 |
| CTI | >= 175 |
| Contact base material | CuSn |
| Contact surface | tinned |
| Constant operating temp., min. | -25 °C |
| Constant operating temp., max. | 100 |

Material data

| | |
|---------------------------------------|--------|
| Storage temperature, min. | -25 °C |
| Storage temperature, max. | 55 °C |
| Max. relative humidity during storage | 80 % |

DIN IEC rating data

| | |
|--|-------|
| Rated current, min. No. pins (Tu=20°C) | 19 A |
| Rated current, max. No. pins (Tu=20°C) | 15 A |
| Rated current, min. No. pins (Tu=40°C) | 16 A |
| Rated current, max. No. pins (Tu=40°C) | 13 A |
| Rated voltage for overvoltage class/pollution severity III/3 | 250 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV |
| Rated voltage for overvoltage class/pollution severity III/2 | 320 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV |
| Rated voltage for overvoltage class/pollution severity II/2 | 400 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 4 kV |

CSA rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

Approvals

Approvals institutes



Classifications

| | |
|------------|-------------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001284 |
| eClass 4.1 | 27-26-07-01 |
| eClass 5.0 | 27-26-07-01 |

Classifications

eClass 5.1

27-26-07-04

Similar products

| Order No. | Part designation | Version |
|------------|---------------------------------|--|
| 1797230000 | SL-SMT5.00/2/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 2, 90°, Box |
| 1840350000 | SL-SMT5.00/2/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 2, 90°, Box |
| 1797240000 | SL-SMT5.00/3/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 3, 90°, Box |
| 1840360000 | SL-SMT5.00/3/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 3, 90°, Box |
| 1797250000 | SL-SMT5.00/4/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 4, 90°, Box |
| 1840370000 | SL-SMT5.00/4/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 4, 90°, Box |
| 1797260000 | SL-SMT5.00/5/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 5, 90°, Box |
| 1840380000 | SL-SMT5.00/5/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 5, 90°, Box |
| 1797270000 | SL-SMT5.00/6/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 6, 90°, Box |
| 1840390000 | SL-SMT5.00/6/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 6, 90°, Box |
| 1797280000 | SL-SMT5.00/7/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 7, 90°, Box |
| 1840400000 | SL-SMT5.00/7/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 7, 90°, Box |
| 1797290000 | SL-SMT5.00/8/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 8, 90°, Box |
| 1840410000 | SL-SMT5.00/8/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 8, 90°, Box |
| 1797300000 | SL-SMT5.00/9/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 9, 90°, Box |
| 1840420000 | SL-SMT5.00/9/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 9, 90°, Box |
| 1797310000 | SL-SMT5.00/10/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 10, 90°, Box |
| 1840430000 | SL-SMT5.00/10/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 10, 90°, Box |
| 1840440000 | SL-SMT5.00/11/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 11, 90°, Box |
| 1797330000 | SL-SMT5.00/12/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 12, 90°, Box |
| 1840450000 | SL-SMT5.00/12/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 12, 90°, Box |
| 1797340000 | SL-SMT5.00/13/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 13, 90°, Box |

| | | |
|------------|---------------------------------|--|
| 1840460000 | SL-SMT5.00/13/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 13, 90°, Box |
| 1797350000 | SL-SMT5.00/14/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 14, 90°, Box |
| 1840470000 | SL-SMT5.00/14/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 14, 90°, Box |
| 1797360000 | SL-SMT5.00/15/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 15, 90°, Box |
| 1840480000 | SL-SMT5.00/15/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 15, 90°, Box |
| 1797370000 | SL-SMT5.00/16/90LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 16, 90°, Box |
| 1840490000 | SL-SMT5.00/16/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 16, 90°, Box |
| 1840500000 | SL-SMT5.00/17/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 17, 90°, Box |
| 1840510000 | SL-SMT5.00/18/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 18, 90°, Box |
| 1840520000 | SL-SMT5.00/19/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 19, 90°, Box |
| 1840530000 | SL-SMT5.00/20/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 20, 90°, Box |
| 1840540000 | SL-SMT5.00/21/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 21, 90°, Box |
| 1840550000 | SL-SMT5.00/22/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 22, 90°, Box |
| 1840560000 | SL-SMT5.00/23/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 23, 90°, Box |
| 1840570000 | SL-SMT5.00/24/90LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.00 mm, No. of poles: 24, 90°, Box |