

SUMMARY



Image is for illustrative purpose only

Wires

Low	3
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

Download

[Request a quote](#)

[Catalog](#)

Series	2C
Termination type	Female solder
IP rating	50
Cable Ø	2.70 - 3.10 mm
Matching parts	FFA.2C.303.CLAC32
Status	
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PCA*: Free receptacle, cable collet
Keying	Hermaphroditic keying ("half moon" insert), plug has male pin 1
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	C32: 2.7 - 3.1 mm
Variant	

Performance

Configuration	2C.303 : 3 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)
Rated Current	15 Amps

Specifications

Contact Type:	Solder
Max. Matings:	1000
Contact Dia.:	1.3 mm (0.051in)
Bucket Dia.:	1 mm (0.039in)
Max. Solid Conductor:	0.5 mm ² (AWG 20)
Max. Stranded Conductor:	0.5 mm ² (AWG 20)

R (max): 3.6 mOhm
 Vtest: 1500 V (AC), 2100 V (DC)

Others

Endurance (Shell): 500 mating cycles
 IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	L
mm.	14	28
in.	0,55	1,10

RECOMMENDED BY LEMO

Tools

None

Cables

CMN.03.T28.031PGCE	PVC	GREY	
CMN.03.T28.031PGZE		Grey	
CMN.03.T28.031PNCE	PVC	Black	
CMN.03.T28.031PNZE			
003 050	PVC	Black	

Property of LEMO SA. All rights reserved
 This document is not contractual

003 081	PVC	Black	
---------	-----	-------	--