



ITEM NO	L
AK670M-1	1000±30MM
AK670M-2	2000±50MM
AK670M-3	3000±50MM
AK670M-5	5000±50MM

ELECTRECAL TEST:

- 1. 100% SHORT, OPEN, MISWIRE TEST
- 2. CONDUCT RESISTANCE: X Ohm (MAX.)
 (0<L<3M:X=2; 3M≤L<10M:X=5; 10M≤L:X=10)
- 3. INSULATION RESISTANCE: 10M Ohm (MIN.)
- 4. DIELECTRIC TEST: AC 300V

④	OUTER MOLD:45P PVC COLOR:BLACK(CS-001)
③	CONNECTOR:MINI USB 4P B PLUG SOLDER TYPE 3U"
②	CONNECTOR:USB A MALE SOLDER TYPE 3U" INSULATION:WHITE
①	CABLE:UL20276,28AWG*1P+28AWG*2C+AL/MY+SPIRAL,O.D:3.8MM PVC JACKET COLOR:BLACK(CS-001)
NO.	DESCRIPTION



Scale		1:1				Name	
TOLERANCE						Drawn	08.29.11
X.X	±0.40					Approved	
X.XX	±0.25						
X.XXX	±0.15						
Angle	±3°						
			Modification	Date	Name		



Item No.		AK670M-X (Version 1.1)	
		AK670M/2-X (Version 2.0)	
Title USB 1.1 & 2.0, USB A Male to USB B Mini (4 pin)			
Drawing No.			
Replace		rev00	
		Sheet	