


THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.



M4 x 0.7 THREAD STANDOFF ENGINEERING KIT				
HEX. =	Threaded Female		Threaded Male/Female	
.236 [6.00]	Aluminum	Nylon	Aluminum	Nylon
Length	Cat. No.	Cat. No.	Cat. No.	Cat. No.
.400 [10.0]	24453	25530	24349	25521
.472 [12.00]	24454	25531	24350	25522
.600 [15.00]	24455	25532	24351	25523
.800 [20.00]	24457	25534	24353	25525
Cat. No. 29321 M4 x 6 mm Slot Drive Machine Screw				



NOTES:

1. A KIT HAS 25 PIECES OF EACH CAT.NO. FOR A TOTAL QUANTITY OF 425 PIECES AND IS HOUSED IN A 16 TRAY, LABELED ENCLOSURE.
2. MAT'L - ALUMINUM, IRIDITE PLATE
MAT'L - NYLON 6/6
3. DRAWS WILL BE ASSEMBLED WITH PLASTIC DIVIDER INSTALLED AND PRODUCT PLACED IN THE FRONT PORTION OF EACH DRAW.
4. SCREWS TO BE PLACED IN THE BACK PORTION OF THE UPPER LEFT MOST DRAW BEHIND MAT'L - STEEL, ZINC PATE

KEYSTONE ELECTRONICS CORP.			
www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME			
HEX 6.0mm STANDOFF HARDWARE KITS			
MATERIAL			
AS NOTED			
FINISH		DRN BY	DATE
AS NOTED		NT	4.19.11
		APP'D	SCALE
		LN	-
TOLERANCES	INCH	[MM]	CODE
DECIMAL	±	[±]	C/M
ANGULAR	±		
UNLESS OTHERWISE SPECIFIED			DWG NO.
			STR-M4

DATE	DESCRIPTION	REV.