


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AF	50	P	LTR	DESCRIPTION	DATE	DWN	APVD
		L		REVISED PER ECR-12-005303	18JUL12	KH	KR



- 1 TAB DIMENSIONS .032±.001x.250
- 2 WIRE STRIP LENGTH .281
- 3 INSULATION SIZE .135 MAX DIA
- △4 DIMENSION DOES NOT INCLUDE TRIM BURR
- △5 DIMENSION DOES NOT INCLUDE TRIM BURR IS ALLOWABLE IN THE SHADED AREA

HOUSING: NYLON, COLOR-RED TRANSLUCENT	2-520103-2
RECEPTACLE: #3 HARD BRASS, TIN	
MATERIAL & FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	P FORTNEY	11/16/88	<b>TE Connectivity</b>
DIMENSIONS: INCHES		CHK	MS FEHER	11/30/88	
		APVD	KA RANDOLPH	12/14/88	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		NAME	
0 PLC ± -		108-2017		TAB ASSEMBLY, ULTRA-FAST, LOOSE PIECE, .250 SERIES, 22-18 AWG	
1 PLC ± -		APPLICATION SPEC			
2 PLC ± -		114-2123			
3 PLC ± .015		WEIGHT	-	SIZE	A3
4 PLC ± -		CUSTOMER DRAWING		CAGE CODE	00779
ANGLES ± -		SCALE		DRAWING NO	C-520103
FINISH		4:1		RESTRICTED TO	-
SEE TABLE		SHEET		1 OF 1	REV
SEE TABLE		L			