



Honeywell Sensing and Control

Home > Products > Thermistors > 173 > Product Page

173-103LAD-301

Surface mounted device 0805



Actual product appearance may vary.

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- RoHS Product List
- Customer Feedback

Features

- Surface mountable for automated pick and place
- Glass-coated ceramic for long term reliability
- Solder plated nickel
- Versatile
- Solderable leads
- Available on tape and reel

Potential Applications

- Consumer electronics
- PCB temperature sensing
- Communications
- Computers
- Rechargeable battery packs
- Low-cost applications with a maximum temperature of 150 °C [302 °F]
- Automotive

Description

173 Series and 175 Series Thermistors are designed to be mounted using robotics onto rigid or flexible PC boards. They are particularly suited for PC boards with a high density of discrete components. The solder-plated, nickel barrier terminations are easily soldered and meet ANSI/J-STD-002 Method B. These products are designed to withstand solder temperatures of 260 °C for 30 seconds. Available on tape and reel for automated assembly.

Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 °F]	10,000 Ohm
Tolerance	±2.0%
Accuracy	25 °C [77 °F]

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

Product Search

Part number search:

Use (*) to expand search

→ Specification Search

R-T Curve	16
Operating Temperature Range	-60 °C to 125 °C [-76 °F to 257 °F]
Maximum Diameter	EIA 0805 SMD
Time Constant in Air	10.0 s
Dissipation Constant	3,5 m/W°C
Series Name	173

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)