

## Specification Sheet

Part Number: 170-03103



Plenum Rated Expandable Braided Sleeving (Halar), .38" Dia, WH, 125 ft/reel

<b>Article Number</b>	170-03103
<b>Type</b>	BSHLR3810
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li><li>• Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.</li><li>• Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
<b>Short Description</b>	Plenum Rated Expandable Braided Sleeving (Halar), .38" Dia, WH, 125 ft/reel

**Global Part Name**

BSHLR3810-PA66E/CTFE-WH

**Length L (Imperial)**

125.0

**Length L (Metric)**

38.1

**Bundle Diameter Min (Imperial)**

0.187

**Bundle Diameter Min (Metric)**

4.8

**Bundle Diameter Max (Imperial)**

0.63

**Bundle Diameter Max (Metric)**

16.0

**Diameter D (imperial)**

0.38

**Diameter D (metric)**

9.5

**Nominal Diameter (Imperial)**

3/8

**Nominal Diameter (Metric)**

9.5

**Material**

Ethylene Chlorotrifluoroethylene (E/CTFE)

**Material Shortcut**

PA66E/CTFE

**Flammability**

FAR 25 UL VW-1

**Halogen free**

No

<b>Operating Temperature (Metric)</b>	-103°F to +302°F (-75°C to +150°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   UL 1441 UL   ANSI/UL 746B UL   UL 746A UL 2024
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	125
<b>Package Quantity (Metric)</b>	38.10
<b>Customs Number</b>	3926909987
<b>Weight (Metric)</b>	0.49
<b>Weight (Imperial)</b>	1.08