



RECOMMENDED P.C.B. PATTERN LAYOUT

NOTE:
 MATERIAL:
 HOUSING:PBT+30% G.F. UL 94V-0
 CONTACT:BRASS
 SHELL:SPCC
 PLATING:
 CONTACT: GOLD FLASH AND TIN OVER NICKEL PLATED
 SHELL: NICKEL PLATED OVER ALL
 SPECIFICATION:
 CURRENT-MAX[AMPS]:1.5A
 VOLTAGE-MAX[VOLTS]:30V
 WITHSTANDING VOLTAGE: 500V AC
 CONTACT RESISTANCE[OHMS]:30 milliohms max
 INSULATION RESISTANCE[OHMS]: 1000 MEGOHMS MIN
 ENVIRONMENTAL
 TEMPERATURE RANGE -55°C~+85°C
 PART NO.:

09/03/20	SYSTEM		NEW DWG			AO			
DATE	DR.BY	ECN.NO.	DESCRIPTION		MARK	VER.			
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表			 TITLE: USB 4P A/M DIP 90° 1U"成品						
X.X	±0.30	X.X°					±3.00°	APPD:	PRODUCT NO: 1001-010-01001
X.XX	±0.15	X.XX°	±1.00°	CHECK:	DATE	SCALE	UNIT	TYPE	PAGE
X.XXX	±0.100	X.XXX°	±0.500°	DRAW:	2009.03.20	1:1	mm	CD	1/1