



Computer Cable, PS/2 Keyboard Cable (KVM Switchbox)

MODEL NUMBER: **P224-010**

Description

Use this 10ft PS/2 cable for any application requiring a male to male connection. Commonly used with PS/2 KVM switches. MiniDIN6 male to MiniDIN6 male. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Superior molded cables with foil-shielding for maximum EMI/RFI protection.
- For KVM switchbox with PS/2 ports (MiniDIN6F)
- MiniDIN6 (male) to MiniDIN6 (male)

Highlights

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- For AT and PS/2 keyboards

System Requirements

- IBM Compatible PC with a PS/2 port - MiniDIN6F
- PS/2 device with a MiniDIN6F port

Package Includes

- 10-ft. PS/2 Keyboard/Mouse Cable MiniDIN6M to MiniDIN6M

Specifications

OVERVIEW	
UPC Code	037332011947
INPUT	
Cable Length (ft.)	10
Cable Length (m)	3.05
PHYSICAL	
Shipping Dimensions (hwd / in.)	11.750 x 7.000 x 1.000
Shipping Dimensions (hwd / cm)	29.84 x 17.78 x 2.54
Shipping Weight (lbs.)	0.3100
Shipping Weight (kg)	0.14
CONNECTIONS	
Side A - Connector 1	MINI DIN-6 (MALE)
Side B - Connector 1	MINI DIN-6 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>