



| | |
|--|------|
| DESIGNED FOR USE WITH .085 SEMI-RIGID CABLE | |
| CABLE ENTRY DIAMETER MINIMUM | |
| HOUSING | .089 |
| CONTACT | .022 |

| REVISIONS | | | |
|-----------------|------------------------|---------|-------------|
| REV | DESCRIPTION | DATE | APPROVED |
| 03 ₂ | REVISED, ECN 95-0127-4 | 3/29/95 | <i>M.A.</i> |

| ELECTRICAL | MECHANICAL | ENVIRONMENTAL |
|--|--|--|
| Nominal Impedance (Ohms) <u>50</u> | Interface Dimensions MIL-STD-348A, Fig. 310.1 | Temperature Rating <u>-65°C to +165°C</u> |
| Frequency Range (GHz) DC to <u>18</u> | Recommended Mating | Vibration MIL-STD-202, Method 204, Condition D. |
| Volt Rating (VRMS MAX) @ Sea Level <u>335</u> | Torque <u>7 - 10 in-lbs</u> | Shock MIL-STD-202, Method 213, Condition I. |
| VSWR <u>1.07 + .01 f(GHz)</u> | Mating Characteristics: | Thermal Shock MIL-STD-202, Method 107, Condition B, |
| Insertion Loss (dB MAX) <u>.03 √f(GHz)</u> | Insertion (MAX Lbs) <u>N/A</u> | Except High Temp +115°C |
| RF Leakage (dB MIN) <u>-90 @ 2-3 GHz</u> | Withdrawal (MIN Oz) <u>N/A</u> | Moisture Resistance MIL-STD-202, Method 106 |
| Corona, 70,000 Ft (VRMS MIN) <u>250</u> | Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u> | Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray |
| Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u> | Center Contact Captivation | |
| Contact Resistance (Milliohms MAX) | Axial (Lbs) <u>6.0</u> | |
| Center Contact <u>3.0</u> | Radial (In-Oz) <u>N/A</u> | |
| Outer Contact <u>2.0</u> | Cable Retention | |
| Cable to Housing <u>0.5</u> | Axial Force (Lbs MIN) <u>30</u> | |
| RF High Potential @ Sea Level | Torque (In-Oz) <u>16</u> | |
| (VRMS MIN @ 5 MHz) <u>670</u> | Weight (Grams) <u>TBD</u> | |
| LR.(Megohms MIN) <u>5,000</u> | | |

| COMPONENT | MATERIAL | FINISH |
|----------------|--|-------------------------------|
| HOUSING | STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 | GOLD PLATE PER MIL-G-45204 |
| COUPLING NUT | STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 | PASSIVATE PER ASTM-A380 |
| DIELECTRIC | TFE FLUOROCARBON PER ASTM-D-1457 | N/A |
| CENTER CONTACT | BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H | GOLD PLATE PER MIL-G-45204 |
| RETAINING RING | BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H | N/A |
| GASKET | SILICONE RUBBER PER ZZ-R-765 | N/A |

| | | | |
|---|--------------------------------|--------------------------------------|---|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | DRAWN BY ED HOYLE | DATE 2/12/86 | AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 |
| TOLERANCE ON | CHECKED BY S. IRONS | DATE 2-27-86 | |
| FRAC. DEC. ANGLES ± 1/64 ±.005 ± ° | APPROVED BY S. IRONS | DATE 2-27-86 | |
| These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission. | USE ASS'Y PROCEDURE | 408-04943 NO. AP20-321 | TITLE OSM STRAIGHT CABLE PLUG DIRECT SOLDER ATTACHMENT |
| | SIZE B | CODE IDENT NO. 26805 | 2001-5431-02 |
| | SCALE 8 : 1 | | REV 03₂ |
| | | | SHEET 1 OF 1 |