

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT 2006 By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00				
P		REVISED PER ECO-11-004835	11MAR11	RK	HMR

.256 DIA MAX

CABLE SUPPORT HOUSING

45°

SHIM

GATE SCREW (BLACK)

CABLE SUPPORT GATE

CROSS RECESSED PAN HEAD, SELF TAPPING SCREW

(1.625)

AMP

SIZE #1 PLUG OR RECEPTACLE REF ONLY

.750

.805 MAX

.640 MAX

1. PARTS PACKAGED UNASSEMBLED.

2 COMPONENTS INDIVIDUALLY BULK PACKED & SHIPPED AS A UNIT PACKAGE KIT.

3 MOLDED PARTS: POLYPROPYLENE, BLACK
SHIM: BRASS
SCREWS: COLD ROLLED STEEL

4 GATE SCREWS: BLACK ZINC PHOSPHATE, SELF-TAPPING SCREWS: ZINC PLATED CLEAR CHROMATE COATING.

COMBINATION DRIVE	2	5205729-3
COMBINATION DRIVE	AS SHOWN	5205729-1
SCREW VERSION	PACKAGING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	22AUG05		TE Connectivity				
DIMENSIONS: INCHES		CHK	22AUG 05		NAME				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	22AUG05		M. WALMSLEY				
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± -		PRODUCT SPEC	-						
MATERIAL		APPLICATION SPEC	-			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
3		FINISH	4			A2	00779	C=5205729	-
CUSTOMER DRAWING		WEIGHT	-			SCALE	SHEET	REV	P
		4:1		1 of 1					

1471-9 (3/11)

5205729