

# F-131P

## Electrical Specifications (@25C)

1. Maximum Power: 1.5 VA
2. Primary: 115V 50/60 Hz
3. Secondary: Series: 8.0V CT @ 0.188 Amps  
 Parallel: 4.0V CT @ 0.376 Amps

## Description:

The F-131P is part of a wide selection of plug-in types that meet the needs of PC boards and solid state power supply design. This transformer can satisfy power as well as control and instrumentation applications.

## Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

## Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings.


## Dimensions:

Units: In inches

A	B	C	D	E
1.187	1.390	1.562	0.312	1.00

Pin length: 0.187 in.  
 Pin size: 0.20 x .041 in.  
 Weight: 3.5 oz

## Schematic:



Primary: 1 to 2  
 Secondary: Series - 3 to 6, Jumper 4 to 5  
 Parallel - 3 to 6, Jumper 3 to 5 and 4 to 6

**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

\*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see <http://www.triadmagnetics.com/faq.html>

