



P.C. BOARD MOUNTING DIMENSIONS  $\Delta$

- $\Delta$  MOLDED PARTS: FLAME RETARDANT, 94V-0 RATED, GLASS FILLED NYLON OR POLYESTER, BLACK  
CONTACTS: BRASS  
HARDWARE: ZINC
- $\Delta$  CONTACTS: SEE TABLE  
HARDWARE: CLEAR CHROMATE
- $\Delta$  GOLD FLASH ON THE MATING SURFACES, .000100 MIN TIN OR TIN-LEAD PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
- $\Delta$  .000030 MIN GOLD PLATE ON THE MATING SURFACES, .000100 MIN TIN OR TIN-LEAD PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.  
-OR-  
GOLD FLASH OVER PALLADIUM-NICKEL PLATE, .000030 MIN TOTAL ON THE MATING SURFACES, .000100 MIN TIN OR TIN-LEAD PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
- $\Delta$  REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.

SUPSD BY 747467-4	WITH SCREWLOCKS	$\Delta$ 4	747467-6
OBSOLETE	WITH SCREWLOCKS	$\Delta$ 3	747467-5
	WITH INSERTS	$\Delta$ 4	747467-4
SUPSD BY 747467-4	WITH INSERTS	$\Delta$ 3	747467-3
	WITH .120 DIA HOLE	$\Delta$ 4	747467-2
	WITH .120 DIA HOLE	$\Delta$ 3	747467-1
REMARKS		FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C RICHARD 7-29-87	TE Connectivity	
DIMENSIONS: INCHES		CHK S WELDON 8-3-87	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD B TAYLOR 8-3-87	PRODUCT SPEC	
0 PLC $\pm$ -		108-40005		
1 PLC $\pm$ -		APPLICATION SPEC		
2 PLC $\pm$ -		114-40015		
3 PLC $\pm$ .005		SIZE CAGE CODE DRAWING NO		
4 PLC $\pm$ -		A1 00779 C=747467		
ANGLES $\pm$ - X		RESTRICTED TO		
MATERIAL $\Delta$ 1	FINISH $\Delta$ 2	WEIGHT -	SCALE 4:1	SHEET 1 OF 1 REV H
CUSTOMER DRAWING				