PHŒNIX CONTACT

Electronic housing - ME 45 UT/BUS/10+2 KMGY - 2200739

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Component housing, length: 99 mm, with vents, Cross connection: integrated bus connector, color: light gray, number of positions cross connector: 10+2

Why buy this product

☑ Item is from the ME product range

☑ Tool-free mounting

☑ Available in overall widths from 12.5 mm to 90 mm, modular extension is possible

☑ Inflammability class V0 according to UL 94

☑ Variety of connection technologies

☑ Can be mounted on the DIN rail

☑ Optional bus connector that is either integrated or mounted on the DIN rail

RoHS

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	50 STK
GTIN	4 046356 666893
GTIN	4046356666893

Technical data

General

Housing type	Component housing
Housing material	Polyamide
Color (RAL)	light gray

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)

Dimensions

Electronic housing - ME 45 UT/BUS/10+2 KMGY - 2200739

Technical data

Dimensions

Length	99 mm

Technical data

Number of positions	32
	8

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values