


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 28JUN ,2005.
 © COPYRIGHT 2005 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
C2		ECR-10-000004	10MAR10	RK	SRE
C3		ECR-10-022205	01FEB11	KK	HMR



- NOTES:**
- MATERIAL:**
 1, INSULATOR - THERMOPLASTIC POLYESTER UL-94-V-0.
 2, SLEEVE - BRASS.
 3, CONTACT - STAMPED BERYLLIUM COPPER.
 - PIN SPECIFICATION:**
 CONTACT ACCEPTS:
 ROUND PIN Ø0.40 TO 0.56.
 RECTANGULAR PIN 0.25 x 0.45 (NOMINAL).
 - MECHANICAL DATA:**
 INSERTION FORCE- 3.2N MAX/CONTACT.
 EXTRACTION FORCE- 0.5N MIN/CONTACT.
 MECHANICAL LIFE- 100 CYCLES MIN (0.75µm Au)
 50 CYCLES MAX (FLASH Au)
 25 CYCLES MAX (5µm Sn)
 CONTACT RETENTION- 3.3N MIN.
 SOLDER PROCESS CAPABILITY-260°C
 - ELECTRICAL:**
 CONTACT RESISTANCE- 10m Ohm MAX.
 CONTACT RATING- 1Amp
 INSULATION RESISTANCE- AT 500V AC BETWEEN ANY 2 ADJACENT CONTACTS MIN 10000m Ohm.
 DIELECTRIC VOLTAGE- MIN 1000V RMS.
 - ENVIRONMENTAL:**
 OPERATION TEMPERATURE- -55 +125°C
 - TUBE PACKAGED WITH NUMBER OF PARTS PER TUBE AS INDICATED IN TABLE. EACH TUBE TO BE INDIVIDUALLY LABELLED. THE LABEL WILL HAVE TE PART NUMBER, XX QTY PER TUBE, DATE CODE AND RoHS DIRECTIVE DETAILS (RoHS 2002/95/EC). OUTER BOX / SHIPPER CARTON TO BE LABELLED WITH TE PART NUMBER, TOTAL XXX QTY PER OUTER BOX / SHIPPER CARTON, DATE CODE AND RoHS DIRECTIVE DETAILS (RoHS 2002/95/EC).**
 - FOR TECHNICAL DATA REFER TO YOUR LOCAL TYCO ELECTRONICS SALES OFFICE.**
 - OBsolete PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI**

Obsolescence	Pin Count	Plating	Plating	Plating	Dimensions	Dimensions	Dimensions	Dimensions	Number Of Positions	Fig	Part No
OBsolete	8	0.75µm Au	0.25µm Au OVER 2-3µm Ni	61.2	17.7	10.6	15.24	48	5	2-1814643-8	
OBsolete	8	FLASH Au	5µm Sn OVER 2-3µm Ni	61.2	17.7	10.6	15.24	48	5	2-1814643-7	
OBsolete	8	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	61.2	17.7	10.6	15.24	48	5	2-1814643-6	
OBsolete	8	0.75µm Au	5µm Sn OVER 2-3µm Ni	61.2	17.7	10.6	15.24	48	5	2-1814643-5	
OBsolete	17	0.75µm Au	0.25µm Au OVER 2-3µm Ni	30.4	10.1	4.8	7.62	24	4	2-1814643-4	
OBsolete	17	FLASH Au	5µm Sn OVER 2-3µm Ni	30.4	10.1	4.8	7.62	24	4	2-1814643-3	
OBsolete	17	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	30.4	10.1	4.8	7.62	24	4	2-1814643-2	
OBsolete	17	0.75µm Au	5µm Sn OVER 2-3µm Ni	30.4	10.1	4.8	7.62	24	4	2-1814643-1	
OBsolete	18	0.75µm Au	0.25µm Au OVER 2-3µm Ni	27.8	10.1	4.8	7.62	22	4	2-1814643-0	
OBsolete	18	FLASH Au	5µm Sn OVER 2-3µm Ni	27.8	10.1	4.8	7.62	22	4	1-1814643-9	
OBsolete	18	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	27.8	10.1	4.8	7.62	22	4	1-1814643-8	
OBsolete	18	0.75µm Au	5µm Sn OVER 2-3µm Ni	27.8	10.1	4.8	7.62	22	4	1-1814643-7	
OBsolete	22	0.75µm Au	0.25µm Au OVER 2-3µm Ni	22.8	17.7	10.6	15.24	18	3	1-1814643-6	
OBsolete	22	FLASH Au	5µm Sn OVER 2-3µm Ni	22.8	17.7	10.6	15.24	18	3	1-1814643-5	
OBsolete	22	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	22.8	17.7	10.6	15.24	18	3	1-1814643-4	
OBsolete	22	0.75µm Au	5µm Sn OVER 2-3µm Ni	22.8	17.7	10.6	15.24	18	3	1-1814643-3	
OBsolete	41	0.75µm Au	0.25µm Au OVER 2-3µm Ni	12.6	17.7	10.6	15.24	10	2	1-1814643-2	
OBsolete	41	FLASH Au	5µm Sn OVER 2-3µm Ni	12.6	17.7	10.6	15.24	10	2	1-1814643-1	
OBsolete	41	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	12.6	17.7	10.6	15.24	10	2	1-1814643-0	
OBsolete	41	0.75µm Au	5µm Sn OVER 2-3µm Ni	12.6	17.7	10.6	15.24	10	2	1814643-9	
OBsolete	41	0.75µm Au	0.25µm Au OVER 2-3µm Ni	12.6	10.1	4.8	7.62	10	1	1814643-8	
OBsolete	41	FLASH Au	5µm Sn OVER 2-3µm Ni	12.6	10.1	4.8	7.62	10	1	1814643-7	
OBsolete	41	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	12.6	10.1	4.8	7.62	10	1	1814643-6	
OBsolete	41	0.75µm Au	5µm Sn OVER 2-3µm Ni	12.6	10.1	4.8	7.62	10	1	1814643-5	
OBsolete	105	0.75µm Au	0.25µm Au OVER 2-3µm Ni	5.0	10.1	4.8	7.62	4	1	1814643-4	
OBsolete	105	FLASH Au	5µm Sn OVER 2-3µm Ni	5.0	10.1	4.8	7.62	4	1	1814643-3	
OBsolete	105	5µm MIN Sn	5µm Sn OVER 2-3µm Ni	5.0	10.1	4.8	7.62	4	1	1814643-2	
OBsolete	105	0.75µm Au	5µm Sn OVER 2-3µm Ni	5.0	10.1	4.8	7.62	4	1	1814643-1	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN: A. Morey 28JUN05
 CHK: S. Parlow 01NOV05
 APVD: F. Wheeler-King 01NOV05
 PRODUCT SPEC: NAME: Tyco Electronics Corporation, Bideford, UK, EX39 4HE
 APPLICATION SPEC: NAME: CLOSED FRAME DIP IC SOCKET

SIZE: A2 CAGE CODE: 00779 DRAWING NO: C=1814643 RESTRICTED TO: -
 WEIGHT: - SCALE: 2:1 SHEET: 1 OF 2 REV: C3
 CUSTOMER DRAWING

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 28JUN ,2005.
 © COPYRIGHT 2005 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
E	B	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

Part No	Fig	Number Of Positions	DIMENSIONS				Sleeve Plating	Contact Plating	No. Of Parts Per Tube	
			A	B	C	D				
2-1814643-9	6	50	22.86	-	25.4	64.7	5µm Sn OVER 2-3µm Ni	0.75µm Au	8	OBSOLETE ⚠
3-1814643-0	6	50	22.86	-	25.4	64.7	5µm Sn OVER 2-3µm Ni	5µm MIN Sn	8	
3-1814643-1	6	50	22.86	-	25.4	64.7	5µm Sn OVER 2-3µm Ni	FLASH Au	8	
3-1814643-2	6	50	22.86	-	25.4	64.7	0.25µm Au OVER 2-3µm Ni	0.75µm Au	8	
3-1814643-3	6	52	22.86	-	25.4	67.2	5µm Sn OVER 2-3µm Ni	0.75µm Au	7	
3-1814643-4	6	52	22.86	-	25.4	67.2	5µm Sn OVER 2-3µm Ni	5µm MIN Sn	7	
3-1814643-5	6	52	22.86	-	25.4	67.2	5µm Sn OVER 2-3µm Ni	FLASH Au	7	
3-1814643-6	6	52	22.86	-	25.4	67.2	0.25µm Au OVER 2-3µm Ni	0.75µm Au	7	
3-1814643-7	6	64	22.86	-	25.4	81.2	5µm Sn OVER 2-3µm Ni	0.75µm Au	6	
3-1814643-8	6	64	22.86	-	25.4	81.2	5µm Sn OVER 2-3µm Ni	5µm MIN Sn	6	
3-1814643-9	6	64	22.86	-	25.4	81.2	5µm Sn OVER 2-3µm Ni	FLASH Au	6	
4-1814643-0	6	64	22.86	-	25.4	81.2	0.25µm Au OVER 2-3µm Ni	0.75µm Au	6	
4-1814643-1	7	32	10.16	-	12.6	40.6	5µm Sn OVER 2-3µm Ni	0.75µm Au	12	
4-1814643-2	7	32	10.16	-	12.6	40.6	5µm Sn OVER 2-3µm Ni	5µm MIN Sn	12	
4-1814643-3	7	32	10.16	-	12.6	40.6	5µm Sn OVER 2-3µm Ni	FLASH Au	12	OBSOLETE
4-1814643-4	7	32	10.16	-	12.6	40.6	0.25µm Au OVER 2-3µm Ni	0.75µm Au	12	
4-1814643-5	7	16/32	10.16	-	12.6	40.6	5µm Sn OVER 2-3µm Ni	0.75µm Au	12	OBSOLETE
4-1814643-6	7	16/32	10.16	-	12.6	40.6	5µm Sn OVER 2-3µm Ni	5µm MIN Sn	12	
4-1814643-7	7	16/32	10.16	-	12.6	40.6	5µm Sn OVER 2-3µm Ni	FLASH Au	12	
4-1814643-8	7	16/32	10.16	-	12.6	40.6	0.25µm Au OVER 2-3µm Ni	0.75µm Au	12	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. Morey 28JUN05	Tyco Electronics Corporation Bideford, UK, EX39 4HE	
DIMENSIONS: mm		CHK S. Parlow 01NOV05	NAME CLOSED FRAME DIP IC SOCKET	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APVD F. Wheeler-King 01NOV05	DRAWING NO A2 00779 C=1814643	
MATERIAL -		FINISH -	WEIGHT -	RESTRICTED TO -
CUSTOMER DRAWING			SCALE 2:1	SHEET 2 OF 2
			REV C3	

1814643