



NOTES:

1. RoHS COMPLIANT
2. FOR WAVESOLDERING (SOLDER BATH TEMPERATURE 260°C FOR 5SEC. AND SOLDER PREHEAT 100°C FOR 30SEC.)
3. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
4. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
5. CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL
6. CAPACITANCE: 830pF ± 20%
7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
8. CONNECTOR IS PART MARKED: 242A10110X CONEC ABC

Directive 2002/95/EC RoHS compliant

|   |  |  |       |             |            |                  |  |            |
|---|--|--|-------|-------------|------------|------------------|--|------------|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND |  |  |       | tolerance   | dim. in mm | scale: 2:1 (5:1) |  |            |
|   |  |  |       | date        |            | name             | material: SEE NOTES  |            |
|   |  |  |       | drawn       | 03.11.11   | Henneboel        | title:<br><b>D-SUB FILTER FEMALE</b><br>25pos. SOLDER PIN STRAIGHT |            |
|   |  |  |       | appd.       | 03.11.11   | Fischer          |  |            |
|   |  |  |       | norm        |            |                  |  |            |
|   |  |  | d-old |             |            | dwg no:          | Inventor 10  | DIN-A3     |
|   |  |  | a     | Original    |            |                  | 24K1A1348  |            |
|   |  |  | rev.  | description | date       | name             | part no:   | 242A10110X |
|   |  |  |       |             |            |                  | sh: 1  |            |
|   |  |  |       |             |            |                  |  |            |