

**FFKDSA1/H-5,08**

Order No.: 1791868

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1791868>

PC terminal block, Nominal current: 6 A, Nom. voltage: 63 V, Pitch: 2.54 mm, Number of positions: 1, Type of connection: Spring-cage conn., Assembly: Soldering, Conductor/PCB connection direction: 0 °, Color: green, The article can be aligned to create different nos. of positions!

Commercial data	
EAN	4017918044473
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.000873 KG
Catalog page information	Page 113 (CC-2009)

## Product notes

WEEE/RoHS-compliant since:  
01/01/2003

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Certificates / Approvals



Certification

CCA, CSA, CUL, GOST, KEMA, UL

**CSA**

Nominal voltage $U_N$	150 V
Nominal current $I_N$	6 A
AWG/kcmil	20

**CUL**

Nominal voltage $U_N$	150 V
Nominal current $I_N$	6 A
AWG/kcmil	26-20

**UL**

Nominal voltage $U_N$	150 V
Nominal current $I_N$	6 A
AWG/kcmil	26-20

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;