


## Crimp contact - CK4,0-ED-1,50BU AG - 1663271

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Turned 4.0 crimp contact, individual female contact, core diameter 1.50 mm<sup>2</sup>, silver-plated



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 123086
Weight per Piece (excluding packing)	2.74 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Electrical characteristics

Note	For HC-M-3 modules
------	--------------------

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

#### Mechanical characteristics

Conductor cross section	1.5 mm <sup>2</sup>
Connection cross section AWG	16
Stripping length of the individual wire	9 mm (9.6 mm (4 - 6 mm <sup>2</sup> )/18 mm (10 mm <sup>2</sup> ))
Insertion/withdrawal cycles	≥ 500

#### General

Type	Individual female contact
Series	HC-M-03
Connection method	Crimp connection

# Crimp contact - CK4,0-ED-1,50BU AG - 1663271

## Technical data

### Material data

Contact material	Copper alloy
Contact surface material	Silver-plated

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

### ETIM

ETIM 2.0	EC000796
ETIM 3.0	EC000796
ETIM 4.0	EC000796
ETIM 5.0	EC000796

### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

## Drawings

Dimensioned drawing

