

## Device connector, front mounting - SM-7EPWN8AAD00 - 1605846

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Device connector, front mounting, angled rotatable, Screw locking, M40, Number of positions: 4+3+PE, Type of contact: Male connector, Crimp connection, Axial O-ring, 4xØ4,4, Shielded: Yes, Flange dimensions: 40 mm x 40 mm, Cable cross section: 0 mm...0 mm



### Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	415.0 GRM
Custom tariff number	85366990
Country of origin	Germany

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121


#### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

# Device connector, front mounting - SM-7EPWN8AAD00 - 1605846


## Drawings

Dimensioned drawing



SM-...PWN8AAD00

Dimensioned drawing



Installation dimensions SM-...PWN8AAD00