



CXXX  
 WEEK NO. FOR YEAR.  
 YEAR NO.  
 "C" FOR MOLEX CHINA  
 DETAIL C

88741-8121	DVI_D-DVI_D DUAL LINK CABLE 5M PARCHMENT WHT	5000 ± 150 196.9 ± 5.9	PARCHMENT WHITE	887808369
88741-8111	DVI_D-DVI_D DUAL LINK CABLE 3M PARCHMENT WHT	3000 ± 80 118.1 ± 3.1	PARCHMENT WHITE	887808369
88741-8101	DVI_D-DVI_D DUAL LINK CABLE 2M PARCHMENT WHT	2000 ± 60 78.7 ± 2.4	PARCHMENT WHITE	887808369
88741-8120	DVI_D-DVI_D DUAL LINK CABLE 5M BLK	5000 ± 150 196.9 ± 5.9	BLACK	887808368
88741-8110	DVI_D-DVI_D DUAL LINK CABLE 3M BLK	3000 ± 80 118.1 ± 3.1	BLACK	887808368
88741-8100	DVI_D-DVI_D DUAL LINK CABLE 2M BLK	2000 ± 60 78.7 ± 2.4	BLACK	887808368
MX P/N	DESCRIPTION	LENGTH	CABLE COLOR	CABLE P/N

ENTER DESCRIPTION EC NO: DG2006-0186 T/DRWN:PDAI 2006/03/09 CHKD: 2006/03/09 APPR:TKAN 2006/03/10	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
				MM/IN	---	METRIC		
				DRAWN BY	DATE	TITLE		
				PDAI	2006/03/07	DVI_D DUAL LINK CABLE		
				CHECKED BY	DATE			
				ZXDENG	2006/03/07			
				APPROVED BY	DATE			
				BORON	2006/03/07			
				MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
				SEE TABLE	SD-88741-002	1 OF 2		
				SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
				A4				

7 6 5 4 3 2 1

E

E

8. CONNECTION DIAGRAM

SHIELD	SHIELD	GROUND
PIN 24	PIN 24	TMDS CLOCK-
PIN 23	PIN 23	TMDS CLOCK+
PIN 22	PIN 22	TMDS CLOCK SHIELD
PIN 21	PIN 21	TMDS DATA 5+
PIN 20	PIN 20	TMDS DATA 5-
PIN 19	PIN 19	TMDS DATA 0/5 SHIELD
PIN 18	PIN 18	TMDS DATA 0+
PIN 17	PIN 17	TMDS DATA 0-
PIN 16	PIN 16	HOT PLUG DETECT
PIN 15	PIN 15	GROUND(+5V )
PIN 14	PIN 14	POWER +5V
PIN 13	PIN 13	TMDS DATA 3+
PIN 12	PIN 12	TMDS DATA 3-
PIN 11	PIN 11	TMDS DATA 1/3 SHIELD
PIN 10	PIN 10	TMDS DATA 1+
PIN 9	PIN 9	TMDS DATA 1-
PIN 7	PIN 7	DDC DATA
PIN 6	PIN 6	DDC CLOCK
PIN 5	PIN 5	TMDS DATA 4+
PIN 4	PIN 4	TMDS DATA 4-
PIN 3	PIN 3	TMDS DATA 2 /4 SHIELD
PIN 2	PIN 2	TMDS DATA 2+
PIN 1	PIN 1	TMDS DATA 2-
DVI_D	DVI_D	CABLE FUNCTION

- NOTE: 1. OVERMOLD SPECIFICATION  
 1.1 DVI BOOT MOLDED WITH SNOW WHITE PVC RESIN P/N IS 887800076.  
 1.2 UL94V-0, COLOR: MAD432  
 1.3 HARDNESS (DUROMETER): SHORE A 90-95  
 2. MECHANICAL SPECIFICATION  
 2.1 CABLE SHOULD STAND THE PULL FORCE 89-111N FOR 30 SECONDS WITH NO VISIBLE TERMINATION DAMAGE.  
 2.2 CABLE SHOULD PASS THE FLEX TEST IN 100 CYCLES AT EACH OF PLANES, PER EIA 364-41, CONDITION I.  
 3. CABLE ELECTRICAL SPECIFICATION  
 3.1 DIELECTRIC STRENGTH: 300VDC FOR 10mS.  
 3.2 INSULATION RESISTANCE: 20 MEGA Ohms  
 3.3 DIFFERENTIAL LINES CHARACTERISTIC IMPEDANCE: 100 ± 7 Ohms @TDR.  
 4. DVI CONNECTOR SPECIFICATION  
 4.1 REFER TO PRODUCT SPEC. PS74320-0001.  
 4.2 CONTACT PLATING: AU FLASH.  
 5. SHORTCIRCUIT AMONG DRAIN WIRES SIGNAL GROUND IS ACCEPTABLE IN DVI CABLE.  
 6. THIS PRODUCT MUST MEET MX RoHS COMPLIANCE.

D

D

C

C

7. MATERIAL LIST

C	DVI THUMB SCREW 887806077
B	DVI_D DUAL CHANNEL G/F CONNECTOR 743230003
A	DVI DULA LINK CABLE (SEE TABLE)
ITEM	DESCRIPTION

B

B

A

A

ENTER DESCRIPTION EC NO: DG2006-0186 T/DRWN:PDAI 2006/03/09 CHKD: 2006/03/09 APPR:TKAN 2006/03/10 DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION																								
	=0 =0	<table border="1"> <tr> <td></td> <td>mm</td> <td>INCH</td> </tr> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>1 PLACE</td> <td>± ---</td> <td>± ---</td> </tr> </table>		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± ---	± ---	1 PLACE	± ---	± ---	MM/IN	---	METRIC										
		mm	INCH																											
	4 PLACES	± ---	± ---																											
3 PLACES	± ---	± ---																												
2 PLACES	± ---	± ---																												
1 PLACE	± ---	± ---																												
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	<table border="1"> <tr> <td>DRAWN BY</td> <td>DATE</td> <td>TITLE</td> </tr> <tr> <td>PDAI</td> <td>2006/03/07</td> <td>DVI_D DUAL LINK CABLE</td> </tr> <tr> <td>CHECKED BY</td> <td>DATE</td> <td></td> </tr> <tr> <td>ZXDENG</td> <td>2006/01/11</td> <td></td> </tr> <tr> <td>APPROVED BY</td> <td>DATE</td> <td></td> </tr> <tr> <td>BORON</td> <td>2006/03/07</td> <td> MOLEX INCORPORATED</td> </tr> <tr> <td>MATERIAL NO.</td> <td>DOCUMENT NO.</td> <td>SHEET NO.</td> </tr> <tr> <td>SEE TABLE</td> <td>SD-88741-002</td> <td>2 OF 2</td> </tr> </table>	DRAWN BY	DATE	TITLE	PDAI	2006/03/07	DVI_D DUAL LINK CABLE	CHECKED BY	DATE		ZXDENG	2006/01/11		APPROVED BY	DATE		BORON	2006/03/07	MOLEX INCORPORATED	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	SEE TABLE	SD-88741-002	2 OF 2	<table border="1"> <tr> <td>SIZE</td> <td>THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td> </tr> <tr> <td>A/4</td> <td></td> </tr> </table>	SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	A/4	
DRAWN BY	DATE	TITLE																												
PDAI	2006/03/07	DVI_D DUAL LINK CABLE																												
CHECKED BY	DATE																													
ZXDENG	2006/01/11																													
APPROVED BY	DATE																													
BORON	2006/03/07	MOLEX INCORPORATED																												
MATERIAL NO.	DOCUMENT NO.	SHEET NO.																												
SEE TABLE	SD-88741-002	2 OF 2																												
SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																													
A/4																														

6 5 4 3 2 1