



Datasheet for part number CA3106E22-4PBF80F0

|                                                                                      |
|--------------------------------------------------------------------------------------|
| Our Catalog Part Number: CA3106E22-4P-B-F80-F0                                       |
| Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA BAYONET |

| Product Datasheet                                   |                                                                                                                       |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Bayonet                                             | Connector with bayonet coupling                                                                                       |
| Shell Style                                         | Plug, straight                                                                                                        |
| Endbell Style                                       | Endbell with clamp and bushing                                                                                        |
| Gender                                              | Pin                                                                                                                   |
| Shell Size                                          | 22                                                                                                                    |
| Contact Arrangement                                 | 22-4                                                                                                                  |
| Number of contacts                                  | 2 contacts size 8, 2 contacts size 12                                                                                 |
| Contact Type                                        | AWG Crimp                                                                                                             |
| Contact Plating                                     | Hard silver                                                                                                           |
| Contacts included                                   | no, delivery without contacts                                                                                         |
| Shielding                                           | no                                                                                                                    |
| Contact Rating at +20 °C (68 °F)<br>(Size 25/12)    | 41 A                                                                                                                  |
| Contact Rating at +20 °C (68 °F)<br>(Size 60/100/8) | 74 A                                                                                                                  |
| Contact Resistance (Size 25/12)                     | 3 mΩ                                                                                                                  |
| Contact Resistance (Size 60/100/8)                  | 1 mΩ                                                                                                                  |
| Wire Cross Section                                  | AWG 8 (Size 8), AWG 14/12 (Size 12)                                                                                   |
| Operating Voltage                                   | In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.  |
| Insulator Resistance                                | Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 MΩ |
| Test Voltage                                        | 2000 Vrms                                                                                                             |
| Air and Creepage Paths (Min)                        | 1,1 mm                                                                                                                |
| Ambient Temperature                                 | Standard insulator material -55°/+125°C (-67/257°F)                                                                   |
| Safety Provisions                                   | IP67 acc. to DIN 40 050 and IP68 (1 bar pressure for 16h)                                                             |
| Salt Spray Resistance                               | 500 hours salt spray resistant                                                                                        |
| Mating Cycles                                       | 500 min                                                                                                               |
| Sep. Force per Contact (Size 25/12)                 | 1,5 N                                                                                                                 |
| Sep. Force per Contact (Size 60/100/8)              | 3,0 N                                                                                                                 |
| Gauge                                               | For infos on Gauge please see catalog VG95234, part 1                                                                 |
| Coupling Torque                                     | Closing: 11 Nm max / Opening: 0,8 Nm min                                                                              |
| Contact Retention (Size 25/12)                      | 55 N                                                                                                                  |
| Contact Retention (Size 60/100/8)                   | 80 N                                                                                                                  |
| Shell Material                                      | Aluminium alloy                                                                                                       |
| Shell Plating                                       | Olive drab chromate over cadmium plating (conductive)                                                                 |
| Insulator and Grommet Material                      | CR-Elastomere                                                                                                         |
| Contact Material                                    | Copper alloy                                                                                                          |
| Harnessing Info: Contact Cross-Section              | <a href="#">See assembly instruction</a>                                                                              |
| Harnessing Info: Insulator Diameter                 | <a href="#">See assembly instruction</a>                                                                              |
| Wire Stripping (Size 25/12)                         | 6,2 mm                                                                                                                |

Specifications and dimensions subject to change.



Datasheet for part number CA3106E22-4PBF80F0

|                                                                                      |
|--------------------------------------------------------------------------------------|
| Our Catalog Part Number: CA3106E22-4P-B-F80-F0                                       |
| Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA BAYONET |

|                                |                                                                               |
|--------------------------------|-------------------------------------------------------------------------------|
| Product Datasheet              |                                                                               |
| Wire Stripping (Size 60/100/8) | 11,8 mm                                                                       |
| General Info                   | <i>All tests in accordance with VG95319 and/or if applicable with VG95210</i> |